

CONDITIONS: STATIC PRESSURE - CONTINUOUS OPERATION

SIDE VIEW

480 VOLTS	MAXIMUM PRESSURE	MAXIMUM VACUUM	MAXIMUM AIRFLOW PRESSURE	MAXIMUM AIRFLOW VACUUM	MINIMUM AIRFLOW PRESSURE	MINIMUM AIRFLOW VACUUM	HORSEPOW	ER	WEIGHT
FLC-12.6	115in. H2O	108in. H2O	379 SCFM	132 SCFM	341 SCFM	0 SCFM	10.7		642 lbs.

480 VOLT, 30 AMP CONNECTION IS REQUIRED.

**END VIEW** 

FLC=FULL LOAD CURRENT

**END VIEW** 

- HOUSE KEEPING PAD IS OPTIONAL (BY OTHERS). THIS IS NOT DESIGNED TO BE HUNG. RECOMMENDED LOCATIONS IN A MECHANICAL AREA. A MINIMUM CLEARANCE OF 36" (THREE SIDES) AND 18" FROM THE HOUSEKEEPING PAD ( OR 21" FROM THE MODULE FRAME) ON THE FOURTH SIDE IS REQUIRED FOR MAINTENANCE & SERVICE ACCESS.
- SOUND LEVEL IS 85 dBA ON 60 Hz UNIT. THE UNIT VIBRATION READING IS LESS THAN 200 CYCLES
  PER 1 MINUTE. SOUND AND VIBRATION TESTS BASED ON THE MODULE MOUNTED DIRECTLY ON A
  CONCRETE FLOOR (WITHOUT HOUSEKEEPING PAD).



1401 Tangier Drive Baltimore, Maryland 21220 T 410.931.8800, F 410.931.4660 800.296.PEVCO (7382), WWW.PEVCO.COM

BLOWER MODULE H-FITTING, WITH OPTIONAL HOUSEKEEPING PAD (ETHERNET COMMUNICATIONS)

SCALE	NONE	DATE
DRAWN	S.S.	12.05.23
REVISED	A.V.	02.26.24
	-	•
DRAWING NUMBER	-	REVISION 1

6" COMPUTERIZED PNEUMATIC TUBE SYSTEMS